


[Home](#)
[About us](#)
[Product](#)
[Warranty](#)
[Contact Us](#)
[email us](#)

► Magnetic Locks

Model No.	Lock Size	Armature Plate Size	Holding Force	Dual Voltage	Power / Current	Available Options	Approvals
S0	182x41x21mm	130x32x21mm	150KG	DC 12V DC 24V	250mA 500mA	N/A	CE/UL
S01 Single	250x42x26mm	200x55x15mm	280KG			LED Timer (0-90sec.) Dry Contact	
S02 Single	266x73x40mm	200x76x15mm	550KG				
S03 Single	285x74x40mm	196x61x16mm	850KG				
S01 Double	500x42x26mm	200x55x15mm	280KG x2				
S02 Double	532x73x40mm	200x76x15mm	550KG x2				
S01 Trim	1007x46x25mm	185x38x12.5mm	280KG				
S02 Trim	1007x68x46mm	200x76x15mm	550KG				
S01GL Weather-resistant	203x44x40mm	158x40x12mm	280KG				
S02GL Weather-resistant	220x63.5x41mm	185x61x16mm	550KG				
S01T Sliding / Mortise	228x38x27mm	185x38x12.5mm	280KG				
S01TS Shear	270x35x30mm	245x35x30mm	250KG		1.6A 900mA		



S0

Mounting Brackets and Extension Hardware

(To match bracket, specify lock model when ordering)

Glass Door Mount/ U Bracket

Suitable for frameless glass door, with a glass thickness of 9-12mm

Adjustable L Plate

L/Z Set (a + b + c)

This accessory is designed for the assembly of the electro-magnets over the door, on the jamb and not on the header. There are three anodized aluminum parts: an 'L' to fasten the electro-magnet, and the two parts of an adjustable 'Z', which receives the strike plate.

Slim extension

L-plate extension

Vital Features of SPRINT Holdfast™ Electro-Magnetic Locks